



GEDORE BEST CHOICE

TORCOFLEX UK 1/2" 3550-UK-LS4

The TORCOFLEX UK 1/2" from GEDORE with test certification to DIN EN ISO 6789:2017 provides controlled screw tightening from 40 to 200 N·m, and is the perfect drive tool for socket inserts. Precise working is guaranteed by the easy-to-use torque adjuster that is set at the end of the handle.

The 1/2" extension piece minimizes scratches on the wing and the size 17, 19 and 21 mm impact sockets with protective sleeve protect the wing.

Controlled tightening and loosening with integrated 1/2" drive - made possible with by the TORCOFLEX with integrated bi-directional operation.

With an actuating accuracy of $\pm 3\%$ tolerance of the set scale value, GEDORE TORCOFLEX actually exceed the DIN EN ISO 6789-2:2017 requirements of $\pm 4\%$.

- 1** **Controlled tightening**
- > Controlled, precision, 40-200 Nm screw tightening
 - > $\pm 3\%$ variation and thus more exacting than the standard-specified $\pm 4\%$

- 2** **Tested quality**
- > Certified in acc. with DIN EN ISO 6789:2017 Part 2
 - > Test certificate included



- 3** **Minimized damage risk**
- > 1/2" extension minimizes the risk of scratches on the wing
 - > Plastic sheathing of the impact sockets protects the wheel rims

- 4** **Easy application**
- > Setting and fixing the torque at the handle end
 - > Clearly audible and tactile torque release

$\pm 3\%$



3550-UK-LS4

TORQUE WRENCH TORCOFLEX UK SET 1/2"

5 pieces

- › Tried-and-tested torque wrench in the 40-200 N·m tightening range with test certificate
- › Controlled clockwise tightening; bi-directional reversible ratchet; 1/2" output drive
- › Classified as per DIN EN ISO 6789-2:2017; adjusted to a maximum permissible +/-3% deviation and thus with a greater precision than the standard-stipulated +/-4%
- › Highly suited for car tyre changing given its 1/2" extension and impact sockets with protective sleeve in the 17, 19 and 21 mm sizes



Code	No.	Square drive inch	Square drive metric mm	Contents	Height mm	Housing - square centre spacing mm	Length mm	Head width mm	Head height mm	pieces	Weight kg
3107027	3550-UK-LS4	1/2"	12.5	Torque wrench TORCOFLEX 40-200 Nm No. 3550-20 UK Extension No. 1990-5 1/2" impact socket set, 3 pieces	44	21.3	499	42.5	22	5	2.398

3549 UK - 3550 UK

TORQUE WRENCH TORCOFLEX UK

1-200 N·m

- › Proven torque wrench in the 1-200 N·m tightening range with test certificate
- › Controlled clockwise tightening; bi-directional reversible ratchet
- › Classified as per DIN EN ISO 6789-2:2017; adjusted to a maximum permissible +/-3% deviation and thus with a greater precision than the standard-stipulated +/-4%



Code	No.	Type	Square drive inch	Square drive metric mm	N·m	Height mm	Housing - square centre spacing mm	Length mm	Head width mm	Head height mm	Weight kg
2958007	3549-00 UK	Reversible ratchet	1/4"	6.3	1 N·m-5 N·m	34	12.5	225	25.0	15	0.61
2958015	3549-02 UK	Reversible ratchet	1/4"	6.3	5 N·m-25 N·m	34	12.5	286	25.0	21.5	0.67
2958023	3549-05 UK	Reversible ratchet	3/8"	10	10 N·m-50 N·m	34	17.5	348	35.0	19.1	0.825
2958031	3550-10 UK	Reversible ratchet	1/2"	12	20 N·m-100 N·m	44	21.25	409	42.5	22	1.38
2958058	3550-20 UK	Reversible ratchet	1/2"	12	40 N·m-200 N·m	44	21.3	522	42.5	22	1.467